



**Gas Furnaces
Split System Air Handlers
Split System High Efficiency
Air Conditioning**

Condensing Units & Heat Pumps

Commercial Package Units

Evaporator Coils

Accessories



INDEX

SPLIT SYSTEM AIR CONDITIONING 1 TO 10 TON

10.0 SEER Side Discharge Mini-Split Condensing Units	1
10.0 SEER Louvered Condensing Units	1
12.0 SEER Louvered Condensing Units	1
13.0 SEER Louvered Condensing Units	2
14.0 SEER Louvered Condensing Units	2
9.0 SEER 7-1/2 and 10 Ton Split System Condensing Units	2
10.0 SEER Through the Wall Condensing Units	2

SPLIT SYSTEM HEAT PUMPS 1 TO 5 TON

10.0 SEER Side Discharge Mini-Split Heat Pumps	3
10.0 SEER Louvered Heat Pumps	3
12.0 SEER Louvered Heat Pumps	3
13.0 SEER Louvered Heat Pumps	3

SPLIT SYSTEM AIR CONDITIONING & HEAT PUMP ADD ON COILS 1-1/2 TO 5 TON

Upflow Evaporator Coils With Cabinet	4
Upflow Evaporator Coils Without Cabinet	4
Horizontal Evaporator Coils	5
Horizontal Two Way Butt-Up Evaporator Coils	5

AIR HANDLERS 1-1/2 TO 10 TON

Ductless Mini-Split Cooling Only Air Handlers	5
Ductless Mini-Split Heat Pump Air Handlers	5
Vertical Wall Mounted Hydronic Air Handlers	5
Multi-Position Electric Heat/Cool Air Handlers	6
Slide-in Electric Heat Kits	6
Ultra High Efficiency Multi Position Heat/Cool Air Handlers	6
Ceiling Mount Air Handlers	7
Ceiling Mount Hydronic Air Handlers	7
Ceiling Mount Hydronic Air Handlers with Water Pump Installed	7
Vertical Wall Mount Upflow Air Handlers	7

GAS-FIRED FURNACES

80% AFUE Induced Draft Multi-Position Gas Furnaces	8
80% AFUE Induced Draft Upflow / Horizontal Left/Right Gas Furnaces	8
80% AFUE Induced Draft Downflow Gas Furnaces	8
90% AFUE Induced Draft 2-Stage Variable Speed Multi-Position Gas Furnaces	8
92.6% AFUE Condensing Multi-Position Gas Furnaces	8

PACKAGED COOLING UNITS 2 TO 15 TON

10.0 SEER Packaged Air Conditioning Units	9
12.0 SEER Packaged Air Conditioning Units	9

PACKAGED HEAT PUMPS 2 TO 5 TON

10.0 SEER Packaged Heat Pumps	10
12.0 SEER Packaged Heat Pumps	10

PACKAGE GAS/ELECTRIC UNITS 2 TO 15 TON

10.0 SEER Single Phase Packaged Units	11
10.0 SEER Three Phase Packaged Units	11
10.0 SEER 460 Volt Packaged Units	12
12.0 SEER Single Phase Packaged Units	12

ACCESSORIES

For All Units	13-15
---------------------	-------

SPLIT SYSTEM AIR CONDITIONING 1 TO 10 TON OUTDOOR UNITS

Model #	(V-PH-HZ) Power Supply	Nominal Ratings		Maximum Overcurrent Protection	Minimum Wire Amp.	Refr. Connection Size		Dimensions (Inch)		
		Cooling Tons	SEER			Liquid	Suction	Height	Width	Depth

10.0 SEER SIDE DISCHARGE MINI-SPLIT CONDENSING UNITS

HDC12-1A	208/240-1-60	1	10	15	7.9	3/8	5/8	20	35	11
HDC18-1A	208/240-1-60	1.5	10	20	14.2	3/8	5/8	25	35	11
HDC24-1A	208/240-1-60	2	10	30	16.6	3/8	5/8	25	35	11

10.0 SEER LOUVERED CONDENSING UNITS

CKL18-1B	208/230-1-60	1.5	10	20	12.5	3/8	3/4	22.5	23	23
CKL24-1F	208/230-1-60	2	10	20	16.4	3/8	3/4	22.5	23	23
CKL30-1E	208/230-1-60	2.5	10	30	18.9	3/8	3/4	22.5	23	23
CKL36-1H	208/230-1-60	3	10	40	21.6	3/8	3/4	25	23	23
CKL36-3A	208/230-3-60	3	10	20	14.2	3/8	3/4	25	23	23
CKL42-1A	208/230-1-60	3.5	10	40	24.1	3/8	7/8	30	23	23
CKL49-1	208/230-1-60	4	10	40	26.8	3/8	7/8	27.5	29	29
CKL49-3	208/230-3-60	4	10	30	17.8	3/8	7/8	27.5	29	29
CKL60-1	208/230-1-60	5	10	50	33.1	3/8	7/8	30	29	29
CKL60-3	208/230-3-60	5	10	30	21.1	3/8	7/8	30	29	29
CKL60-4	460-3-60	5	10	15	11.1	3/8	7/8	30	29	29
CKL62-1	208/230-1-60	5	10	60	36.1	3/8	7/8	37.5	29	29

12.0 SEER LOUVERED CONDENSING UNITS

CLJ18-1	208/230-1-60	1.5	12	20	10.9	3/8	3/4	25	23	23
CLJ24-1	208/230-1-60	2	12	20	14.5	3/8	3/4	30	23	23
CLJ30-1	208/230-1-60	2.5	12	30	16.2	3/8	3/4	25	29	29
CLJ36-1A	208/230-1-60	3	12	30	19.5	3/8	3/4	27.5	29	29
CLJ42-1A	208/230-1-60	3.5	12	40	22.5	3/8	3/4	30	29	29
CLJ48-1	208/230-1-60	4	12	50	29.0	3/8	7/8	30	29	29
CLJ60-1	208/230-1-60	5	12	50	33.1	3/8	7/8	40	29	29

SPLIT SYSTEM AIR CONDITIONING 1 TO 10 TON OUTDOOR UNITS

Model #	(V-PH-HZ) Power Supply	Nominal Ratings		Maximum Overcurrent Protection	Minimum Wire Amp.	Refr. Connection Size		Dimensions (Inch)		
		Cooling Tons	SEER			Liquid	Suction	Height	Width	Depth

13.0 SEER *SUPER QUIET* LOUVERED CONDENSING UNITS

CLT24-1A	208/230-1-60	2	13	20	12.9	3/8	3/4	25	29	29
CLT30-1A	208/230-1-60	2.5	13	30	16.2	3/8	3/4	30	29	29
CLT36-1A	208/230-1-60	3	13	30	20.1	3/8	7/8	30	29	29
CLT42-1A	208/230-1-60	3.5	13	40	22.4	3/8	7/8	37.5	29	29
CLT48-1A	208/230-1-60	4	13	40	24.1	3/8	7/8	40	29	29
CLT60-1	208/230-1-60	5	13	50	26.5	3/8	7/8	40	29	29

14.0 SEER *SUPER QUIET* LOUVERED CONDENSING UNITS

CLQ24-1A	208/230-1-60	2	14	20	12.9	3/8	3/4	30	29	29
CLQ30-1A	208/230-1-60	2.5	14	30	16.2	3/8	3/4	30	29	29
CLQ36-1	208/230-1-60	3	14	30	18.5	3/8	7/8	37.5	29	29
CLQ42-1	208/230-1-60	3.5	14	40	21.8	3/8	7/8	30	35-1/2	35-1/2
CLQ48-1	208/230-1-60	4	14	50	24.1	3/8	7/8	35	35-1/2	35-1/2
CLQ60-1	208/230-1-60	5	14	50	28.5	3/8	7/8	40	35-1/2	35-1/2

9.0 SEER 7-1/2 AND 10 TON SPLIT SYSTEM CONDENSING UNITS

CKL090-3	208/230-3-60	7.5	9	60	37.8	5/8	1-3/8	40	35.5	35.5
CKL120-3	208/230-3-60	10	9	60	43.3	5/8	1-3/8	40	35.5	35.5
CKL090-4	460-3-60	7.5	9	30	18.8	5/8	1-3/8	40	35.5	35.5
CKL120-4	460-3-60	10	9	35	22.2	5/8	1-3/8	40	35.5	35.5

10.0 SEER THROUGH THE WALL SPLIT SYSTEM CONDENSING UNITS

TWC18-1	208/230-1-60	1.5	10	20	9.6	3/8	3/4	32	24	18-3/4
TWC24-1	208/230-1-60	2	10	30	17.7	3/8	3/4	32	24	18-3/4
TWCR30-1	208/230-1-60	2.5	10	40	18.2	3/8	3/4	32	24	18-3/4

SPLIT SYSTEM HEAT PUMPS 1 TO 5 TON OUTDOOR UNITS

Model #	(V-PH-HZ) Power Supply	Nominal Ratings			Maximum Overcurrent Protection	Minimum Wire Amp.	Refr. Connection Size		Dimensions (Inch)		
		Cooling Tons	SEER	HSPF			Liquid	Suction	Height	Width	Depth

10.0 SEER SIDE DISCHARGE MINI-SPLIT HEAT PUMPS

HDP12-1A	208/240-1-60	1	10.0	6.8	15	7.9	3/8	5/8	25	35	11
HDP18-1A	208/240-1-60	1.5	10.0	6.8	20	14.2	3/8	5/8	25	35	11
HDP24-1A	208/240-1-60	2	10.0	6.8	30	16.6	3/8	5/8	25	35	11

10.0 SEER LOUVERED SPLIT SYSTEM HEAT PUMPS

CPL18-1	208/230-1-60	1.5	10.0	6.8	20	12.6	3/8	3/4	22.5	23	23
CPL24-1A	208/230-1-60	2	10.0	7.0	30	15.7	3/8	3/4	30	23	23
CPL30-1	208/230-1-60	2.5	10.0	6.8	30	18.9	3/8	3/4	30	23	23
CPL36-1	208/230-1-60	3	10.0	7.3	30	22.7	3/8	3/4	25	29	29
CPL42-1	208/230-1-60	3.5	10.0	7.5	40	25.8	3/8	7/8	30	29	29
CPL48-1	208/230-1-60	4	10.0	7.5	40	26.8	3/8	7/8	32.5	29	29
CPL48-3	208/230-3-60	4	10.0	7.5	30	17.8	3/8	7/8	32.5	29	29
CPL60-1	208/230-1-60	5	10.0	8.0	50	33.1	3/8	7/8	32.5	29	29
CPL60-3	208/230-3-60	5	10.0	8.0	30	21.1	3/8	7/8	32.5	29	29

12.0 SEER LOUVERED SPLIT SYSTEM HEAT PUMPS

CPLJ18-1	208/230-1-60	1.5	12.0	7.0	20	10.9	3/8	3/4	32.5	23	23
CPLJ24-1	208/230-1-60	2	12.0	7.5	20	15.3	3/8	3/4	25	29	29
CPLJ30-1	208/230-1-60	2.5	12.0	7.5	30	19.3	3/8	3/4	25	29	29
CPLJ36-1	208/230-1-60	3	12.0	7.8	30	18.5	3/8	3/4	30	29	29
CPLJ42-1	208/230-1-60	3.5	12.0	8.0	40	24.2	3/8	7/8	37.5	29	29
CPLJ48-1	208/230-1-60	4	12.0	8.0	40	24.7	3/8	7/8	40	29	29
CPLJ60-1A	208/230-1-60	5	12.0	8.0	50	33.1	3/8	7/8	40	29	29

13.0 SEER SUPER QUIET LOUVERED SPLIT SYSTEM HEAT PUMPS

CPLT24-1A	208/230-1-60	2	13.0	7.3	20	14.5	3/8	3/4	30	29	29
CPLT30-1A	208/230-1-60	2.5	13.0	7.8	30	17.8	3/8	3/4	25	29	29
CPLT36-1	208/230-1-60	3	13.0	8.0	30	20.1	3/8	7/8	27.5	29	29
CPLT42-1	208/230-1-60	3.5	13.0	8.4	40	22.4	3/8	7/8	30	29	29
CPLT48-1	208/230-1-60	4	13.0	8.4	40	24.6	3/8	7/8	30	35.5	35.5
CPLT60-1	208/230-1-60	5	13.0	8.4	50	28.5	3/8	7/8	35	35.5	35.5

SPLIT SYSTEM AIR CONDITIONING & HEAT PUMP 1-1/2 TO 5 TON EVAPORATOR COILS

Model #	Nominal Cooling Tons	Overall Dimension (Inch)			Air Inlet Dimensions		Fitting Size	
		Height	Width	Depth	Width	Depth	Liquid	Suction

UPFLOW EVAPORATOR COILS WITH CABINET (FOR AIR CONDITIONING OR HEAT PUMP)

U-18	1.5	14	14-1/4	21-1/8	7	16-3/4	3/8	5/8
U-29	2-2.5	14	14-1/4	21-1/8	7	16-3/4	3/8	3/4
U-30	2.5	16	18-1/4	21-1/8	7	16-3/4	3/8	3/4
U-31	2.5	14	14-1/4	21-1/8	7	16-3/4	3/8	3/4
U-32	2.5	18	18-1/4	21-1/8	7	16-3/4	3/8	3/4
U-35	3	18-1/8	14-1/4	21-1/8	7	16-3/4	3/8	3/4
U-36	3	17-3/4	18-1/4	21-1/8	11	16-3/4	3/8	3/4
U-42	3.5	18	18-1/4	21-1/8	11	16-3/4	3/8	3/4
U-47	4	22	18-1/4	21-1/8	11	16-3/4	3/8	7/8
U-49	4	27	21-1/8	21-1/8	11	16-3/4	3/8	7/8
U-59	5	27	21-1/8	21-1/8	11	16-3/4	3/8	7/8
U-60	5	21 1/2	24-1/4	21-1/8	13-1/4	19-3/4	3/8	7/8
U-61	5	22 1/8	24-1/4	21-1/8	13-1/4	19-3/4	3/8	7/8
U-62	5	27	21-1/8	21-1/8	13-1/4	19-3/4	3/8	7/8

UPFLOW EVAPORATOR COILS WITHOUT CABINET

UC-18	1.5	14 1/4	13	20-1/8	7	16-3/4	3/8	5/8
UC-29	2-2.5	14	13	20-1/8	7	16-3/4	3/8	3/4
UC-32	2.5	17-7/8	13	20-1/8	7	16-3/4	3/8	3/4
UC-35	3	18-1/4	13	20-1/8	7	16-3/4	3/8	3/4
UC-36	3	17-1/2	17	20-1/8	11	16-3/4	3/8	3/4
UC-42	3.5	17-3/4	17	20-1/8	11	16-3/4	3/8	3/4
UC-47	4	22-1/8	17	20-1/8	11	16-3/4	3/8	7/8
UC-49	4	21-7/8	19-3/4	20-1/8	12-7/8	16-3/4	3/8	7/8
UC-59	5	25-7/8	19-3/4	20-1/8	11	16-3/4	3/8	7/8
UC-60	5	21-1/4	20-1/4	23	13-1/4	19-3/4	3/8	7/8
UC-61	5	22	20-1/4	23	13-1/4	19-3/4	3/8	7/8
UC-62	5	26-1/8	19-3/4	20-1/8	13-1/4	19-3/4	3/8	7/8

SPLIT SYSTEM AIR CONDITIONING & HEAT PUMP 1-1/2 TO 5 TON EVAPORATOR COILS

Model #	Nominal Cooling Tons	Overall Dimension (Inch)			Air Inlet Dimensions		Fitting Size	
		Height	Width	Depth	Width	Height	Liquid	Suction

HORIZONTAL EVAPORATOR COILS

H-24F	2	25	13-1/2	25-1/2	16	21	3/8	3/4
H-36F	3	25	13 1/2	25-1/2	16	21	3/8	3/4
H-49F	4.5	25	13 1/2	33-1/2	24	21	3/8	7/8
H-60F	5	25	13 1/2	39-1/2	30	21	3/8	7/8
H-61F	5	25	13 1/2	39-1/2	30	21	3/8	7/8

HORIZONTAL TWO WAY BUTT-UP EVAPORATOR COILS

HT-1830	1.5-2.5	14	21-1/8	21-1/2	19-7/8	12-3/4	3/8	3/4
HT-3236	2.5-3	14	21-1/8	21-1/2	19-7/8	12-3/4	3/8	3/4
HT-36	3	17-1/2	21-1/8	21-1/2	19-7/8	16-1/4	3/8	3/4
HT-4248	3.5-4	17-1/2	21-1/8	21-1/2	19-7/8	16-1/4	3/8	3/4
HT-4860	5-Apr	21	24	27-7/8	22-3/4	19-3/4	3/8	7/8
HT-61	5	21	24	27-7/8	22-3/4	19-3/4	3/8	7/8

SPLIT SYSTEM AIR CONDITIONING & HEAT PUMP 1-1/2 TO 5 TON EVAPORATOR COILS

Model #	Power Supply	Cooling Capacity	Electric Heating Capacity	Nominal CFM @.2 Static Pres.	Dimensions (Inch)			Refr. Connection	
					Height	Width	Depth	Liquid	Suction

DUCTLESS MINI-SPLIT COOLING ONLY AIR HANDLERS

WMC09-1A	208/240-1-60	1	---	270	14.2	33.4	6.0	1/4	3/8
WMC12-1A	208/240-1-60	1	---	290	14.2	33.4	6.0	1/4	3/8
WMC18-1A	208/240-1-60	1.5	---	420	14.6	41.4	7.4	3/8	5/8
WMC24-1A	208/240-1-60	2	---	540	14.6	41.4	7.4	3/8	5/8

DUCTLESS MINI-SPLIT HEAT PUMP AIR HANDLERS

WMH12-1A	208/240-1-60	1	---	290	14.2	33.4	6.0	1/4	3/8
WMH18-1A	208/240-1-60	1.5	---	420	14.6	41.1	7.4	3/8	5/8
WMH24-1A	208/240-1-60	2	---	540	14.6	41.1	7.4	3/8	5/8

VERTICAL WALL MOUNTED HYDRONIC AIR HANDLERS

AH1826-1	115-1-60	1.5	18,400	620	39-3/4	20-3/16	16-1/8	3/8	5/8
AH2429-1	115-1-60	2	20,600	760	39-3/4	20-3/16	16-1/8	3/8	5/8
AH3043-1FR	115-1-60	2.5	30,500	1020	44-1/4	24	21	3/8	3/4
AH3645-1FR	115-1-60	3	32,000	1120	44-1/4	24	21	3/8	3/4

ELECTRIC HEAT/COOL AIR HANDLERS 1-1/2 TO 5 TON

Model #	Power Supply	Cooling Capacity	Nominal CFM @.2 Static Pres.	Dimensions (Inch)			Refr. Connection	
				Height	Width	Depth	Liquid	Suction

MULTI POSITION AIR HANDLERS

AR18-1	208/240-1-60	1.5	600	41-1/8	15-1/2	22	3/8	5/8
AR24-1	208/240-1-60	2	900	41-1/8	15-1/2	22	3/8	3/4
AR30/32-1	208/240-1-60	2.5	1100	41-1/8	15-1/2	22	3/8	3/4
AR36-1	208/240-1-60	3	1300	46-3/4	19-1/2	22	3/8	3/4
AR42-1	208/240-1-60	3.5	1500	46-3/4	19-1/2	22	3/8	3/4
AR48/49-1	208/240-1-60	4	1600	53-1/4	22	24	3/8	7/8
AR60/61-1	208/240-1-60	5	2100	53-1/4	22	24	3/8	7/8

SLIDE IN ELECTRIC HEAT KITS FOR AR/AER UNITS 1-1/2 TO 5 TON

HKR-03	3 KW-Single Phase
HKR-05	5 KW-Single Phase
HKR-05C	5 KW w/ Circuit breaker-Single Phase
HKR-06	6 KW-Single Phase
HKR-08	8 KW-Single Phase
HKR-08C	8 KW w/Circuit breaker-Single Phase
HKR-10	10 KW-Single Phase
HKR-10C	10 KW w/ Circuit breaker-Single Phase
HKR-15C	15 KW w/ Circuit breaker-Single Phase
HKR-20C	20 KW w/ Circuit breaker-Single Phase
HKR-21C	21 KW w/ Circuit breaker-Single Phase
HKR3-15	15 KW-Single Phase (AR units only)
HKR3-20	20 KW-Three Phase (AR units only)

ULTRA HIGH EFFICIENCY HEAT/COOL AIR HANDLERS 2 TO 5 TON

Model #	Power Supply	Cooling Capacity	Nominal CFM @.2 Static Pres.	Dimensions (Inch)			Refr. Connection	
				Height	Width	Depth	Liquid	Suction

ULTRA HIGH EFFICIENCY MULTI POSITION AIR HANDLERS

AR18-1	208/240-1-60	1.5	600	41-1/8	15-1/2	22	3/8	5/8
AR24-1	208/240-1-60	2	900	41-1/8	15-1/2	22	3/8	3/4
AR30/32-1	208/240-1-60	2.5	1100	41-1/8	15-1/2	22	3/8	3/4
AR36-1	208/240-1-60	3	1300	46-3/4	19-1/2	22	3/8	3/4
AR42-1	208/240-1-60	3.5	1500	46-3/4	19-1/2	22	3/8	3/4
AR48/49-1	208/240-1-60	4	1600	53-1/4	22	24	3/8	7/8
AR60/61-1	208/240-1-60	5	2100	53-1/4	22	24	3/8	7/8

CEILING MOUNT ELECTRIC HEAT/COOL AIR HANDLERS 1-1/2 TO 3 TON

Model #	Power Supply	Cooling Capacity	Nominal CFM @ .2 Static Pres.	Dimensions (Inch)			Refr. Connection	
				Height	Width	Depth	Liquid	Suction

CEILING MOUNT AIR HANDLERS

AC18-00C	208/230-1-60	1.5	710	10	37-1/4	21	3/8	3/4
AC18-05C	208/230-1-60	1.5	710	10	37-1/4	21	3/8	3/4
AC18-06C	208/230-1-60	1.5	710	10	37-1/4	21	3/8	3/4
AC18-08C	208/230-1-60	1.5	710	10	37-1/4	21	3/8	3/4
AC24-00C	208/230-1-60	2	880	10	37-1/4	21	3/8	3/4
AC24-05C	208/230-1-60	2	880	10	37-1/4	21	3/8	3/4
AC24-06C	208/230-1-60	2	880	10	37-1/4	21	3/8	3/4
AC24-08C	208/230-1-60	2	880	10	37-1/4	21	3/8	3/4
AC24-10C	208/230-1-60	2	880	10	37-1/4	21	3/8	3/4
AC30-00C	208/230-1-60	2.5	1015	10	43-1/4	21	3/8	3/4
AC30-05C	208/230-1-60	2.5	1015	10	43-1/4	21	3/8	3/4
AC30-08C	208/230-1-60	2.5	1015	10	43-1/4	21	3/8	3/4
AC30-10C	208/230-1-60	2.5	1015	10	43-1/4	21	3/8	3/4
AC36-00C	208/230-1-60	3	1150	10	49-1/4	21	3/8	3/4
AC36-05C	208/230-1-60	3	1150	10	49-1/4	21	3/8	3/4
AC36-08C	208/230-1-60	3	1150	10	49-1/4	21	3/8	3/4
AC36-10C	208/230-1-60	3	1150	10	49-1/4	21	3/8	3/4

CEILING MOUNT HYDRONIC AIR HANDLERS

ACH1819-1	115-1-60	1.5	623	10	39-1/2	21	3/8	3/4
ACH2423-1	115-1-60	2	769	10	39-1/2	21	3/8	3/4
ACH3028-1	115-1-60	2.5	1028	10	45-1/2	21	3/8	3/4

CEILING MOUNT HYDRONIC AIR HANDLERS WITH WATER PUMP INSTALLED

ACHP1819-1	115-1-60	1.5	623	10	40-1/4	21	3/8	3/4
ACHP2423-1	115-1-60	2	769	10	40-1/4	21	3/8	3/4
ACHP3028-1	115-1-60	2.5	1028	10	46-1/4	21	3/8	3/4
ACHP3632-1	115-1-60	3	1181	10	58	21	3/8	3/4

VERTICAL WALL MOUNT UPFLOW AIR HANDLERS 1-1/2 TO 3 TON

Model #	Power Supply	Cooling Capacity	Nominal CFM @ .2 Static Pres.	Dimensions (Inch)			Refr. Connection	
				Height	Width	Depth	Liquid	Suction

VERTICAL WALL MOUNT UPFLOW AIR HANDLERS

AWB18-00C	208/240	1.5	771	36	20-3/16	16-1/8	3/8	5/8
AWB18-03C	208/240	1.5	771	36	20-3/16	16-1/8	3/8	5/8
AWB18-05C	208/240	1.5	771	36	20-3/16	16-1/8	3/8	5/8
AWB18-08C	208/240	1.5	771	36	20-3/16	16-1/8	3/8	5/8
AWB24-00C	208/240	2	850	36	20-3/16	16-1/8	3/8	5/8
AWB24-05C	208/240	2	850	36	20-3/16	16-1/8	3/8	5/8
AWB24-08C	208/240	2	850	36	20-3/16	16-1/8	3/8	5/8
AWB24-10C	208/240	2	850	36	20-3/16	16-1/8	3/8	5/8
AWB30-00C	208/240	2.5	1087	36	20-3/16	16-1/8	3/8	5/8
AWB30-03C	208/240	2.5	1087	36	20-3/16	16-1/8	3/8	5/8
AWB30-05C	208/240	2.5	1087	36	20-3/16	16-1/8	3/8	5/8
AWB30-08C	208/240	2.5	1087	36	20-3/16	16-1/8	3/8	5/8
AWB30-10C	208/240	2.5	1087	36	20-3/16	16-1/8	3/8	5/8
AWB36-00CFR	208/240	3	1349	36	24	21	3/8	3/4
AWB36-05CFR	208/240	3	1349	36	24	21	3/8	5/8
AWB36-08CFR	208/240	3	1349	36	24	21	3/8	5/8
AWB36-10CFR	208/240	3	1349	36	24	21	3/8	5/8

GAS-FIRED FURNACES

Model #	Available Cooling Tons	Heating Capacity MBTU/HR +		AFUE %	Dimensions (Inch)			Outlet		Flue (Inch)
		Input	Output		Height	Width	Depth	Width	Depth	Dia.

80% AFUE MULTI-POSITION INDUCED DRAFT GAS FURNACES (Upflow / Horizontal)

GMT045-3A	3	45	36	80.0	39	14	28	12-1/2	19-5/8	4
GMT070-3A	3	70	56	80.0	39	14	28	12-1/2	19-5/8	4
GMT070-4A	4	70	56	80.0	39	17-1/2	28	16	19-5/8	4
GMT090-3A	3	90	72	80.0	39	17-1/2	28	16	19-5/8	4
GMT090-4A	4	90	72	80.0	39	17-1/2	28	16	19-5/8	4
GMT090-5A	5	90	72	80.0	39	21	28	19-1/2	19-5/8	4
GMT115-5A	5	115	92	80.0	39	21	28	19-1/2	19-5/8	4
GMT140-5A	5	140	108	80.0	39	24-1/2	28	23	19-5/8	4

80% AFUE MULTI-POSITION INDUCED DRAFT GAS FURNACES (Upflow / Horizontal Left or Right)

GMTH045-3A	3	45	36	80.0	39	14	28	12-1/2	19-5/8	4
GMTH070-4A	4	70	56	80.0	39	17-1/2	28	16	19-5/8	4
GMTH115-5A	5	115	92	80.0	39	21	28	19-1/2	19-5/8	4

80% AFUE INDUCED DRAFT GAS FURNACES (Downflow)

GDT045-3A	3	45	36	80.0	39	14	28	12-1/2	19-5/8	4
GDT070-3A	3	70	56	80.0	39	14	28	12-1/2	19-5/8	4
GDT090-4A	4	90	72	80.0	39	17-1/2	28	16	19-5/8	4
GDT115-4A	4	115	100	80.0	39	21	28	19-1/2	19-5/8	4

92.6% AFUE CONDENSING MULTI-POSITION GAS FURNACES (Upflow / Downflow / Horizontal)

GMNT040-3	3	40	37	92.6	46	14	28	12-1/2	19-5/8	2*
GMNT060-3	3	60	55	92.6	46	14	28	12-1/2	19-5/8	2*
GMNT080-4	4	80	74	92.6	46	17-1/2	28	16	19-5/8	3*
GMNT100-4	4	100	92	92.6	46	21	28	19-1/2	19-5/8	3*
GMNT120-5	5	120	111	92.6	46	24-1/2	28	23	19-5/8	3*

* Schedule 40 PVC or DWV

90% AFUE INDUCED DRAFT 2-STAGE MULTI-POSITION GAS FURNACE (Variable Speed)

Model #	Available Cooling Tons	Heating Capacity MBTU/HR +				Dimensions (Inch)			Outlet		Flue (Inch)
		Low Fire		High Fire		Height	Width	Depth	Width	Depth	Dia.
		Input	Output	Input	Output						
GMNTE060-3	3	36	32.6	60	54	46	14	28	12-1/2	19-5/8	2
GMNTE080-4	4	48	43.4	80	72	46	17-1/2	28	16	19-5/8	3
GMNTE100-4	4	60	54.3	100	90	46	21	28	19-1/2	19-5/8	3

PACKAGED COOLING UNITS 2 TO 10 TON

Model #	Power Supply	Cooling Capacity Tons	SEER	Nominal CFM	Dimensions (Inch)			Maximum Supplemental Heat Electric KW (Access.)	Overcurrent Protection AMPS
					Height	Width	Depth		

10.0 SEER PACKAGED AIR CONDITIONING UNITS

PCK024-1	208/230-1-60	2	10.0	800	27	24	56-1/4	10	30
PCK030-1	208/230-1-60	2.5	10.0	1000	27	24	56-1/4	10	30
PCK036-1	208/230-1-60	3	10.0	1200	27	24	56-1/4	15	40
PCK042-1	208/230-1-60	3.5	10.0	1400	29-5/8	32	63	20	40
PCK048-1	208/230-1-60	4	10.0	1600	29-5/8	32	63	20	50
PCK060-1	208/230-1-60	5	10.0	2000	34-5/8	32	63	20	60
PCK036-3	208/230-3-60	3	10.0	1200	27	24	56-1/4	20	20
PCK048-3	208/230-3-60	4	10.0	1600	29-5/8	32	63	20	30
PCK060-3	208/230-3-60	5	10.0	2000	34-5/8	32	63	20	40
PCK060-4	460-3-60	5	10.0	2000	34-3/8	32	63	20	20
PCBO90-3	208/230-3-60	7.5	9.0*	3000	36	74-9/16	74-9/16	40	60
PCBO90-4	460-3-60	7.5	9.0*	3000	36	74-9/16	74-9/16	40	30
PCB120-3	208/230-3-60	10	9.0*	4000	52	74-9/16	74-9/16	40	80
PCB120-4	460-3-60	10	9.0*	4000	52	74-9/16	74-9/16	40	40
PCB150-3	208/230-3-60	12.5	8.6*	5000	52	74-9/16	74-9/16	40	80
PCB150-4	460-3-60	12.5	8.6*	5000	52	74-9/16	74-9/16	40	45
PCB180-3	208/230-3-60	15	8.5*	5600	52	74-9/16	74-9/16	40	110
PCB180-4	460-3-60	15	8.5*	5600	52	74-9/16	74-9/16	40	60

*EER

12.0 SEER PACKAGED AIR CONDITIONING UNITS

PCKJ024-1A	208/230-1-60	2	12.0	800	27	24	56-1/4	10	20
PCKJ030-1	208/230-1-60	2.5	12.0	1000	27	24	56-1/4	15	30
PCKJ036-1	208/230-1-60	3	12.0	1200	29-5/8	32	63	20	30
PCKJ042-1A	208/230-1-60	3.5	12.0	1400	29-5/8	32	63	20	40
PCKJ048-1	208/230-1-60	4	12.0	1600	34-5/8	32	63	20	40
PCKJ060-1	208/230-1-60	5	12.0	2000	34-5/8	32	63	20	60

PACKAGED HEAT PUMP UNITS 2 TO 5 TON

Model #	Power Supply	Cooling Capacity Tons	SEER	Nominal CFM	Dimensions (Inch)			Maximum Supplemental Heat Electric KW (Access.)	Overcurrent Protection AMPS
					Height	Width	Depth		

10.0 SEER PACKAGED HEAT PUMP UNITS

PHK024-1	208/230-1-60	2	10.0	800	27	24	56-1/4	10	30
PHK030-1	208/230-1-60	2.5	10.0	1000	27	24	56-1/4	10	30
PHK036-1	208/230-1-60	3	10.0	1200	29-5/8	32	63	15	40
PHK042-1	208/230-1-60	3.5	10.0	1400	34-5/8	32	63	20	40
PHK048-1	208/230-1-60	4	10.0	1600	34-5/8	32	63	20	50
PHK060-1	208/230-1-60	5	10.0	2000	34-5/8	32	63	20	60
PHK036-3	208/240-3-60	3	10.0	1200	29-5/8	32	63	15	20
PHK048-3	208/240-3-60	4	10.0	1600	34-5/8	32	63	20	30
PHK060-3	208/240-3-60	5	10.0	2000	34-5/8	32	63	20	40

12.0 SEER PACKAGED HEAT PUMP UNITS

PHKJ024-1A	208/230-1-60	2	12.0	800	29-5/8	32	63	10	20
PHKJ030-1	208/230-1-60	2.5	12.0	1000	29-5/8	32	63	15	30
PHKJ036-1	208/230-1-60	3	12.0	1200	34-5/8	32	63	20	30
PHKJ042-1	208/230-1-60	3.5	12.0	1400	34-5/8	32	63	20	40
PHKJ048-1A	208/230-1-60	4	12.0	1600	34-5/8	32	63	20	50
PHKJ060-1A	208/230-1-60	5	11.0	2000	34-5/8	32	63	20	60

PACKAGED GAS / ELECTRIC UNITS 2 TO 10 TON

Model #	Power Supply	Cooling Capacity Tons	SEER	Heating Input MBH	AFUE % / S.S. EFF.	Nominal CFM	Blower	Minimum Wire Amp	Maximum Fuse Size	Dimensions (Inch)			Horizontal			
													Supply		Return	
													Height	Width	Height	Width

10.0 SEER SINGLE PHASE MODELS

PGB024050-1	208/230-1-60	2	10.0	46	80.0	900	1/5	17.9	25	31-1/8	38-3/4	52	15	13-3/8	15	18-3/8
PGB024075-1	208/230-1-60	2	10.0	69	80.0	900	1/5	17.9	25	31-1/8	38-3/4	52	15	13-3/8	15	18-3/8
PGB030050-1A	208/230-1-60	2.5	10.0	46	80.0	1050	1/3	21.4	35	31-1/8	38-3/4	52	15	13-3/8	15	18-3/8
PGB030075-1A	208/230-1-60	2.5	10.0	69	80.0	1050	1/3	21.4	35	31-1/8	38-3/4	52	15	13-3/8	15	18-3/8
PGB030100-1A	208/230-1-60	2.5	10.0	92	80.0	1050	1/3	21.4	35	31-1/8	43-3/4	52	15	13-3/8	15	20-3/8
PGB036050-1A	208/230-1-60	3	10.0	46	80.0	1200	1/3	26.8	40	31-1/8	38-3/4	52	15	13-3/8	15	18-3/8
PGB036075-1A	208/230-1-60	3	10.0	69	80.0	1200	1/3	26.8	40	31-1/8	38-3/4	52	15	13-3/8	15	18-3/8
PGB036100-1A	208/230-1-60	3	10.0	92	80.0	1200	1/3	26.8	40	31-1/8	43-3/4	52	15	16-3/8	15	20-3/8
PGB042075-1A	208/230-1-60	3.5	10.0	69	80.0	1450	1/2	32.7	50	31-5/8	43-3/4	52	15	16-3/8	15	20-3/8
PGB042100-1A	208/230-1-60	3.5	10.0	92	80.0	1450	1/2	32.7	50	31-5/8	43-3/4	52	15	16-3/8	15	20-3/8
PGB042125-1	208/230-1-60	3.5	10.0	115	80.0	1450	1/2	29.9	50	33-5/8	58-1/2	55-3/8	17	24-5/8	17	26-5/8
PGB048075-1A	208/230-1-60	4	10.0	69	80.0	1700	1/2	30.3	50	33-5/8	58-1/2	55-3/8	17	24-5/8	17	26-5/8
PGB048125-1A	208/230-1-60	4	10.0	115	80.0	1700	1/2	30.3	50	33-5/8	58-1/8	55-3/8	17	24-5/8	17	26-5/8
PGB048150-1A	208/230-1-60	4	10.0	140	80.0	1700	1/2	30.3	50	33-5/8	58-1/8	55-3/8	17	24-5/8	17	26-5/8
PGB060100-1	208/230-1-60	5	10.0	92	80.0	1950	3/4	43.7	60	33-5/8	58-1/8	55-3/8	17	24-5/8	17	26-5/8
PGB060125-1	208/230-1-60	5	10.0	115	80.0	1950	3/4	43.7	60	33-5/8	58-1/8	55-3/8	17	24-5/8	17	26-5/8
PGB060150-1	208/230-1-60	5	10.0	140	80.0	1950	3/4	43.7	60	33-5/8	58-1/8	55-3/8	17	24-5/8	17	26-5/8

THREE PHASE MODELS

PGB036075-3A	208/230-3-60	3	10.0	69	82	1200	1/3	17.1	25	31-1/8	38-3/4	52	15	13 3/8	15	18-3/8
PGB048100-3A	208/230-3-60	4	10.0	92	82	1700	1/2	23.0	35	33-5/8	55-3/8	58-1/8	17	24-5/8	17	26-5/8
PGB048150-3A	208/230-3-60	4	10.0	140	82	1700	1/2	23.0	35	33-5/8	55-3/8	58-1/8	17	24-5/8	17	26-5/8
PGB060100-3	208/230-3-60	5	10.0	92	82	1950	3/4	28.4	40	33-5/8	55-3/8	58-1/8	17	24-5/8	17	26-5/8
PGB060125-3	208/230-3-60	5	10.0	115	82	1950	3/4	28.4	40	33-5/8	55-3/8	58-1/8	17	24-5/8	17	26-5/8
PGB060150-3	208/230-3-60	5	10.0	140	82	1950	3/4	28.4	40	33-5/8	55-3/8	58-1/8	17	24-5/8	17	26-5/8
PGB090210-3	208/230-3-60	7.5	9.0*	210	78	3000	1 1/2	44.2	60	36	74-9/16	74-9/16	12-1/5	40	17-9/16	40
PGB102210-3A	208/230-3-60	8.5	9.0*	210	78	3400	2	49.4	60	36	74-9/16	74-9/16	12-1/5	40	17-9/16	40
PGB120245-3	208/230-3-60	10	9.0*	245	78	4000	3	61.9	80	52	74-9/16	74-9/16	20-1/4	40	25-13/16	40
PGB150245-3	208/230-3-60	12.5	8.6*	245	78	5000	5	68.4	80	52	74-9/16	74-9/16	20-1/4	40	25-13/16	40
PGB180280-3	208/230-3-60	15	8.5*	280	78	5600	5	98.0	110	52	74-9/16	74-9/16	20-1/4	40	25-13/16	40

*EER

PGB MODELS MEET CALIFORNIA NOx REQUIREMENTS

1. IN ACCORDANCE WITH D.O.E. TEST PROCEDURES
2. CERTIFIED PER ARI 210
3. BTU/WATT @ 80/67 F INSIDE - 95 F OUTSIDE AIR

PACKAGED GAS / ELECTRIC UNITS 2 TO 15 TON

Model #	Power Supply	Cooling Capacity Tons	SEER	Heating Input MBH	AFUE % / S.S. EFF.	Nominal CFM	Blower	Minimum Wire Amp	Maximum Fuse Size	Dimensions (Inch)			Horizontal			
													Supply		Return	
										Height	Width	Depth	Height	Width	Height	Width

460 VOLT MODELS

PGB060150-4	460-3-60	5	10.0	140	82	1950	3/4	13.4	20	33 5/8	55-5/8	58-1/8	17	24-5/8	17	26-5/8
PGB090210-4	460-3-60	7.5	9.0*	210	78	3000	1-1/2	22.0	30	36	74-9/16	74-9/16	12-1/2	40	17-9/16	40
PGB102210-4A	460-3-60	8.5	9.0*	210	78	3400	2	23.6	35	36	74-9/16	74-9/16	12-1/2	40	17-9/16	40
PGB120245-4	460-3-60	10	9.0*	245	78	4000	3	29.8	40	52	74-9/16	74-9/16	20-1/4	40	25-13/16	40
PGB150245-4	460-3-60	12.5	8.6*	245	78	5000	5	33.2	45	52	74-9/16	74-9/16	20-1/4	40	25-13/16	40
PGB180280-4	460-3-60	15	8.5*	280	78	5600	5	47.5	60	52	74-9/16	74-9/16	20-1/4	40	25-13/16	40

*EER

PGB MODELS MEET CALIFORNIA NOx REQUIREMENTS

1. IN ACCORDANCE WITH D.O.E. TEST PROCEDURES
2. CERTIFIED PER ARI 210
3. BTU/WATT @ 80/67 F INSIDE - 95 F OUTSIDE AIR

12.0 SEER SINGLE PHASE MODELS

PGJ024050-1A	208/230-1-60	2	12.0	46	80	800	1/2	19.4	30	31-1/8	43-3/4	52	15	16-3/8	15	20-3/8
PGJ024075-1A	208/230-1-60	2	12.0	69	80	800	1/2	19.4	30	31-1/8	43-3/4	52	15	16-3/8	15	20-3/8
PGJ030050-1A	208/230-1-60	2.5	12.0	46	80	1000	1/2	21.1	30	31-1/8	43-3/4	52	15	16-3/8	15	20-3/8
PGJ030075-1A	208/230-1-60	2.5	12.0	69	80	1000	1/2	21.1	30	31-1/8	43-3/4	52	15	16-3/8	15	20-3/8
PGJ036075-1A	208/230-1-60	3	12.0	69	80	1200	1	27.4	40	33-5/8	55-3/8	58-1/8	17	24-5/8	17	26-5/8
PGJ036100-1A	208/230-1-60	3	12.0	92	80	1200	1	27.4	40	33-5/8	55-3/8	58-1/8	17	24-5/8	17	26-5/8
PGJ042075-1A	208/230-1-60	3.5	12.0	69	80	1400	1	32.3	50	33-5/8	55-3/8	58-1/8	17	24-5/8	17	26-5/8
PGJ042100-1A	208/230-1-60	3.5	12.0	92	80	1400	1	32.3	50	33-5/8	55-3/8	58-1/8	17	24-5/8	17	26-5/8
PGJ048075-1	208/230-1-60	4	12.0	69	80	1500	1	33.3	50	33-5/8	55-3/8	58-1/8	17	24-5/8	17	26-5/8
PGJ048100-1	208/230-1-60	4	12.0	92	80	1500	1	33.3	50	33-5/8	55-3/8	58-1/8	17	24-5/8	17	26-5/8

ACCESSORIES

MODEL #	DESCRIPTION
---------	-------------

THERMOSTATS

HT18-60	Heating Only
CT18-60	Cooling Only
CHT18-60	Cooling / Heating
HPT18-60	Heat Pump
HPTA18-60	Automatic Heat Pump
CHT90-120	Two Stage Clg. / Htg (PG/PCO90 & 120)

HEAT PUMP ACCESSORIES

AFE18-60	All Fuel Kit
OT18-60	Outdoor Thermostat Kit
EH18-60	Emergency Heat Relay Kit
HSPK-01	Shut-Off Relay for AC Airhandlers
FP-01	Freeze Protection Kit-AH Air Handlers
OT/EHR18-60	Outdoor Thermostat Kit with Emergency Heat Relay

L.P. CONVERSION KITS

LPW-04	For W.R. Valve with 100% Ignition Models Or Standing Pilot Models
LPW-05	For PGO 90/120
LPW-06	For PGB 90/180
LPM-01	For PGB Series and Gas Furnaces
LPM-03	For GSM Series Gas Furnaces
LPM-04	For GSMS Series Gas Furnaces
LPT-00	For GMT/GDT Series Gas Furnaces
LPT-01	For GMNT Series Gas Furnaces

DOWNFLOW FURNACE COMBUSTIBLE FLOOR BASE

SBT14	For GMT/GDT/GMNT Models (14" wide)
SBT17	For GMT/GDT/GMNT Models (17" wide)
SBT21	For GMT/GDT/GMNT Models (21" wide)
SBT24	For GMT/GDT/GMNT Models (24" wide)

SLIDE IN ELECTRIC HEAT KITS

FOR PCK/PHK UNITS 2-5 TON

HK05-1	5 KW-Single Phase
HK08-1	8 KW-Single Phase
HK10-1	10 KW-Single Phase
HK15-1	15 KW-Single Phase
HK20-1	20 KW-Single Phase
HK05-3	5 KW-Three Phase
HK10-3	10 KW-Three Phase
HK15-3	15 KW-Three Phase
HK20-3	20 KW-Three Phase
HK20-4	20 KW-460 Volt

DOWNFLOW COIL KITS

DFKT-14	For 14" Wide Furnaces
DFKT-17	For 17" Wide Furnaces
DFKT-21	For 21" Wide Furnaces
DFKT-24	For 24" Wide Furnaces

MODEL #	DESCRIPTION
---------	-------------

SLIDE IN ELECTRIC HEAT KITS

FOR PCB UNITS 7-1/2 - 15 TON

HKCB20-3	20 KW - Three Phase
HKCB30-3	30 KW - Three Phase
HKCB40-3	40 KW - Three Phase
HKCB20-4	20 KW - Three Phase
HKCB30-4	30 KW - Three Phase
HKCB40-4	40 KW - Three Phase

-3 208/260 Volt, -4 480 Volt

SLIDE IN ELECTRIC HEAT KITS

AIR HANDLERS FOR AR90/120 7-1/2 & 10 TON

AHKD15-3	15 KW - Three Phase - 208-230
AHKD20-3	20 KW - Three Phase - 208-230
AHKD30-3	30 KW - Three Phase - 208-230
AHKD15-4	15 KW - Three Phase - 460
AHDK20-4	20 KW - Three Phase - 460
AHKD30-4	30 KW - Three Phase - 460

EXPANSION VALVE KITS

XV18-36C	Non-Bleed Type Expansion Valve
XV42-60C	Non-Bleed Type Expansion Valve
XVB18-36C	Bleed Type Expansion Valve
XVB42-60C	Bleed Type Expansion Valve

START KITS

SK-1	Fits CE19 & 36"E"
SK-2	Fits CE25 & 30
SK-3	Fits CE42 & 48
SK-5	Fits CE36"F"
SK-10	Start Kits - various units
SK-11	Start Kits - various units
SK-12	Start Kits - various units
SK-13	Start Kits - various units
SK-14	Start Kits - various units
SK-15	Start Kits - various units
SK-16	Start Kits - various units
SK-17	Start Kits - various units
SK-18	Start Kits - various units
SK-19	Start Kits - various units
SK-20	Start Kits - various units
SK-21	Start Kits - various units
SK-22	Start Kits - various units
SK-23	Start Kits - various units
SK-24	Start Kits - various units

SVB-80	Side Vent Blower GMP/ GMPV only
CVK-00	Concentric Duct Kit for GSMS, GMNT

ACCESSORIES (continued)

MODEL #	DESCRIPTION
---------	-------------

PCK/PCKJ/PHK/PHKJ – SMALL CHASSIS

PCP-1	Plenum Kit
PCCP-1	Curb & Platform Kit
PCE-1	Fully Modulating Economizer (Slide In)
SQRPC-1	Square to Round Converter – Down Discharge
SQRPCH-1	Square to Round Converter – Horiz. Discharge
PCMD-1	Manual Damper
PCEF-1	Elbow & Flashing Kit
LPAK-00	Louver Panel Accessory Kit

PCK/PCKJ/PHK/PHKJ – MEDIUM & LARGE CHASSIS

PCP2-3	Plenum Kit
PCCP2-3	Curb & Platform
PCE2-3	Fully Modulating Economizer (Slide In)
SQRPC2-3	Square to Round Converter – Down Discharge
SQRPCH-2	Square to Round Converter – Horiz. Discharge for Medium Chassis
SQRPCH-3	Square to Round Converter – Horiz. Discharge for Large Chassis
PCMD2-3	Manual Damper
PCEF2-3	Elbow & Flashing Kit
LPAK-01	Louver Panel Accessory Kit – Medium Chassis
LPAK-02	Louver Panel Accessory Kit – Large Chassis, 71.75"
LPAK-03	Louver Panel Accessory Kit – Large Chassis, 77"

PGB, PGJ 2- 5 TON MODELS

PGC-1	Roof Curb
PGC-2	Roof Curb
PGC-3	Roof Curb
PGED-1	Downflow Economizer
PGED-2	Downflow Economizer
PGED-3	Downflow Economizer
PGEH-1	Horizontal Economizer
PGEH-2	Horizontal Economizer
PGEH-3	Horizontal Economizer
PGMD1-3	25% Manual Fresh Air Damper
PGMDM1-3	25% Motorized Fresh Air Damper
CDK1-2	Concentric Duct Kit
CDK-3	Concentric Duct Kit
SQRPG-1	Square To Round Converter
SQRPG-2	Square To Round Converter
SQRPG-3	Square To Round Converter
PGFR-1	Downflow Filter Rack
PGFR-2	Downflow Filter Rack

ROOFTOP ACCESSORIES

PGB/PCB 7-1/2 - 15 TON MODELS

PGC-5	Roof Curb
PGED090/120-5	Down Flow Economizer 7 1/2 and 8 1/2 Ton Models
PGED120/180-5	Down Flow Economizer 10-15 Ton Models
PGEH090/102-5	Horizontal Economizer 7 1/2 and 8 1/2 Ton Models
PGEH120/180-5	Horizontal Economizer 10-15 Ton Models
PGMD-5	25% Manual Fresh Air Damper
PGMDM-5	25% Motorized Fresh Air Damper
CDK90	Concentric Duct Kit 7 1/2 Ton
CDK120	Concentric Duct Kit 10 Ton
CDK150	Concentric Duct Kit 12 1/2 Ton
CDK180	Concentric Duct Kit 15 Ton
SQRPG090-5	Square To Round Converter 7 1/2 and 8 1/2 Ton Models
PGCT120-5	Concentric Transition 10-15 Ton
PGP-5	4" Plenum Drops With Cap
PGHDK090/102-5	Horizontal Conversion Kit 7 1/2 and 8 1/2 Ton Models
PGHDK120/180-5	Horizontal Conversion Kit 10 and 15 Ton Models
PLK090/102-5	Panel Louver Kit 7 1/2 and 8 1/2 Ton Models
PLK120/180-5	Panel Louver Kit 10 and 15 Ton Models

MISCELLANEOUS - PGB

LA-01	Low Ambient Kit
HLPK-01	High & Low Pressure Switch Kit

PGB/PGJ/PCB ACCESSORY CODE

CHASSIS #1	CHASSIS #2	CHASSIS #3
PGB024050	PGB030100	PGB042125
PGB024075	PGB036100	PGB048075
PGB030050	PGB042075	PGB048100
PGB030075	PGB042100	PGB048125
PGB036050		PGB048150
PGB036075	PGJ024050	PGB060100
	PGJ024075	PGB060125
	PGJ030050	PGB060150
	PGJ030075	
CHASSIS #5		PGJ036075
PGB09210		PGJ036100
PGB120245		PGJ042075
PGB180280		PGJ042100
PCB090		PGJ048075
PCB120		PGJ048100

*Note: There are 2 different chassis heights.

- 1.) 090/102 models are 36" high
- 2.) 120/180 models are 52" high

ACCESSORIES (continued)

MODEL #	DESCRIPTION
---------	-------------

CEILING ACCESS PANELS FOR AC AIR HANDLER

CAP-1	Solid Panel / Small Chassis
CAP-2	Solid Panel / Medium Chassis
CAP-3	Solid Panel / Large Chassis
CAP-4	Solid Panel / X-Large Chassis
CAP-1L	Louvered Panel / Small Chassis
CAP-2L	Louvered Panel / Medium Chassis
CAP-3L	Louvered Panel / Large Chassis
CAP-4L	Louvered Panel / X-Large Chassis

WALL ACCESS DOORS FOR AH,AW AIR HANDLERS

WAD-1	Small Access Door
WAD-2	Large Access Door

PERMANENT AIR FILTERS FOR AR/AER AIR HANDLERS

FIL18-32	Filter for Small Chassis
FIL36-42	Filter For Medium Chassis
FIL48-61	Filter for Large Chassis

